

CENTER 305



Features

- Triple Display
- Time Function
- RS-232 Interface
- With Window Software
- 16,000 Records Data logger
- Auto Power Off
- REL Function
- HOLD Function
- MAX MIN Function
- Resolution 0.1°C 0.1°F
- Low Battery Indication

CENTER 306



Features

- Dual Input
- Triple Display
- Time Function
- RS-232 Interface
- With Window Software
- 16,000 Records Data logger
- Auto Power Off
- HOLD Function
- MAX MIN Function
- Resolution 0.1°C 0.1°F
- Low Battery Indication

Range and Accuracy

-200°C~1370°C..±0.2%rdg+1°C
-328°F~2498°F..±0.2%rdg+2°F

Operation Condition

0°C~50°C(32°F~122°F)
0%~80%RH(0°C~35°C,32°F~95°F)
0%~60%RH(35°C~50°C,95°F~122°F)

Storage Temperature

-20°C~60°C

Input Protection

60V DC or 24Vrms AC Maximum

Battery

9V,NEDA1604,IEC 6F22,JIS 006P

Dimension

184mmX64mmX30mm(7.25"X2.5"X1.2")

Weight

Approx.210g

Optional Accessories



CENTER®

CENTER TECHNOLOGY CORP.

4/F., No.415, Jung-Jeng Rd., 238 Shu-Lin Chien, Taipei, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http : //www.centertek.com

Distributed by: